



Name: _____

Date: _____

1. To load on a conveyor truck start from:
 - a. The front of the head board down to the back of the conveyor
 - b. The back of the conveyor to the front of the head board
 - c. The middle of the conveyor to the front of the head board
 - d. The middle of the conveyor to the back of the conveyor

2. Improperly securing a load can result in citations.
 - a. True
 - b. False

3. The load should always be checked with the first:
 - a. 25 miles of your trip
 - b. 100 miles of your trip
 - c. 50 miles of your trip
 - d. 75 miles of your trip

4. Always make sure wheels are "Chocked" before loading.
 - a. True
 - b. False

5. It is okay to place cribbing or outrigger pads on the battery box.
 - a. True
 - b. False

6. Always make sure conveyor is properly secured by using a single strap over the conveyor belt while in transit.
 - a. True
 - b. False

7. Pallets should be positioned on the bed butted against each other with no material in between.
 - a. True
 - b. False



Name: _____

Date: _____

8. When climbing onto the trailer you can climb up using:
 - a. The tires
 - b. The pallets
 - c. The approved ladder
 - d. Never climb onto the trailer

9. Never have your drop or tag axle down when transporting material.
 - a. True
 - b. False

10. If you are loading a truck with a crane mounted at the rear of the truck, start at the headboard and load your heaviest products positioned close to the head board and work your way to the back.
 - a. True
 - b. False